

ECO-CEM
High Performance, Low Carbon

**BRIDGEMAN
CONCRETE** **55**
ESTABLISHED 1967
OVER 55 YEARS OF SERVICE TO THE INDUSTRY

HR CEMENT limited

ECOMAX

LOW-CARBON  CONCRETE

A true replacement of embodied carbon cement



Introducing New Zealand's environmentally friendly concrete

ECOMAX

LOW-CARBON  CONCRETE

Introduction to Eco-Max Concrete

Eco-Cem is made locally in the Bay of Plenty, right here in New Zealand. Eco-Max is made with a mix of Eco-Cem and Xtra-Cem (GP) cement to create a superior concrete with 20-65 percent less carbon.

Concrete mix designs can be customized allowing you to balance construction aspects such as setting time, strength gain, finishing and cost. It's not only an environmentally friendly choice, it's more durable and has an enhanced design life.



Key Benefits



High Performance

Eco-Cem cement has a creamier finish and shrinks less, therefore produce better foundations, floors and precast panels.



Durability

Eco-Max is hard wearing with a denser finish meaning a longer design life and better chemical and stain resistance.



Low Shrinkage

Concrete made with Eco-Cem has a lower shrinkage performance.



Cost Competitive

Eco-Max is a cost competitive product with standard GP Cement.



Reduced Thermal Expansion

Eco-Cem is ideal for large concrete pours as it reduces the risk of thermal cracking.



Reduced Alkali Aggregate Reaction

Eco-Cem helps to minimise the risk of alkali-silica reaction in concrete.



Superior Finish

Pozzolanic cements have a creamier and denser finish which create an overall superior finish to your concrete projects.



Lower Embodied Carbon

The SCMs (Supplementary Cementitious Materials) substitutes the cement and creates 20-65% less embodied carbon which means we are doing our part to create a sustainable future for New Zealand.



True GP Cement Replacement

Eco-Max concrete can replace up to 70% of GP cement. GP cement contains **823kgs** of embodied carbon per tonne, where Eco-Cem contains only **120kgs** per tonne.



Proven
performance
worldwide

Available SCM/Pozzolan Options

	Recycled SCM			Natural SCM
	BFS - Blast Furnace Slag <i>steel industry</i>	Fly Ash <i>power industry</i>	Silica Fume <i>numerous sources</i>	Pumice/Volcanic ash
Substitution rates	Up to 65%	20-30%	<10%	<25%
Availability	Not previously available	Local: available May-November only Imported: high container prices means no imports	Imported	Not commercially available. Fully investigated by HR Cement but not commercially viable
Price	We can produce this product at a cost-competitive price.	Local: similar price as cement Imported: much more expensive	to 80%)	to 80%)
NZS3101:2006 Durability	Yes	Yes	Yes	No



Hardworking
concrete that's easy
on the planet

ECO-CEM

Specifying and Designing

- ▶ NZS3104:2021 allows for 56 day testing of concrete with SCM
- ▶ NZS3101 - durability, 65% BFS mixes
- ▶ Eco-Max % replacement can be specified on a project basis
- ▶ Cement substitutions with Eco-Max

A Change in Philosophy

With the introduction of this innovative product into the New Zealand market, the design and build process will need to adapt accordingly in line with a more sustainable product that is recognised and proven globally.

Collaboration is Key

Working together alongside engineers, architects, contractors and ready mix is key to ensure the right balance of application for various seasons and onsite demands to maximise the dose of Eco-Cem.



Embodied Carbon Reduction

We have developed the ratings in the graph below to give you an indication of our Embodied Carbon reductions across various products.

	20 MPa	25 MPa	30 MPa	35 MPa	40 MPa	45 MPa	50 MPa
ISC 2020 Baseline	284	313	347	391	441	495	550
ECO-MAX - 15% Replacement CO₂ Reduction	193 32%	224 28%	236 32%	270 31%	285 35%	320 35%	342 38%
ECO-MAX - 25% Replacement CO₂ Reduction	176 38%	205 35%	215 38%	246 37%	259 41%	291 41%	310 44%
ECO-MAX - 35% Replacement CO₂ Reduction	159 44%	184 41%	193 44%	221 43%	233 47%	261 47%	278 49%
ECO-MAX - 45% Replacement CO₂ Reduction	142 50%	165 47%	172 50%	197 50%	207 53%	232 53%	247 55%
ECO-MAX - 55% Replacement CO₂ Reduction	125 56%	144 54%	151 56%	173 56%	181 59%	202 59%	216 61%
ECO-MAX - 65% Replacement CO₂ Reduction	108 62%	125 60%	130 63%	148 62%	155 65%	173 65%	184 66%

Global Warming Potential (GWP)
(Embodied carbon per m³)

ISC 2020 Baseline is from the Infrastructure Sustainability Council 2020 Baseline.

CO₂ Reduction % is calculated from the ISC 2020 Baseline.

Percentage replacement values have been calculated from our inhouse LCA Mix calculator reviewed and verified by thinkstep Ltd.

Above values are calculated on 20mm Standard mixes for Auckland, other regions and mixes will vary slightly.

For technical information please refer to HR Cement Ltd product data sheet for Eco-Cem.

For more information on suitability and achievable CO₂ reductions please contact your local representative.



Get in Touch

Cameron Boulton
Bridgeman Concrete
Auckland Sales Manager

M: 027 419 9974
E: cameron@bridgeman.co.nz

Paul Martinovich
Bridgeman Concrete
Auckland Sales Manager

M: 027 897 3256
E: paul@bridgeman.co.nz



Environmental Product Declaration

An Environmental Product Declaration (EPD) is an independently produced report of the effects across a wide variety of criteria. The EPD for our GP Cement Xtra-cem was produced by Thinkstep, a well known and very reputable NZ based company, and published in February 2022.



Up to a 65% reduction in our carbon footprint when compared with standard GP cement.

